Haier Biomedical
Intelligent Protection of Life Science

-150°C Cryo Freezer



DW-150W209A

Innovative Design

- 100% Hydrocarbon refrigeration technology
- Quiet, low noise operation
- Energy-efficient and Environmentally-friendly
- Safe and reliable
- Intelligent control

Qingdao Haier Biomedical Co., Ltd.

No.280 Fengyuan Road, High-tech Zone,
Qingdao, 266111, Shandong, P.R. China
E-mail: inquiry@haierbiomedical.com
Website: www.haiermedical.com

Oct, 2026

Haier Biomedical
Haier Biomedical International
Haier Biomedical International
Haier Biomedical International
Haier Biomedical International

Product Advantages

Hydrocarbon energy-saving refrigeration technologies

- Includes specialist industrial compressor, hydrocarbon refrigerant, dual-compressors 4-stage cascade refrigeration system, which delivers excellent energy-efficiencies
- Energy-efficient fan design with intelligent start/stop

Environmentally friendly

- HC refrigerant, truly environmentally-friendly refrigeration system with zero global warming potential (GWP)
- Eco-friendly insulation foam has low GWP and is significantly lower than most HFCs commonly used, offering better environmental protection

Superior Uniformity

The temperature uniformity is ±5°C with the setting temperature of -150°C

Safe, Secure and Reliable

The pressure state of the system can be automatically adjusted by the pressure controller to prevent the pressure from being too high to effect the freezer operation. Multiple alarms, including high and low temperature, power failure, door ajar, hot condenser, low battery, sensor error, and high ambient temperature.

Low noise


Noise-reduction features and system ensure a low noise output of just 55dB

Functional Details

Integrated stainless steel hinge
Lid opening with stopping mechanism, angle >45°



Intelligent touchscreen controller and multiple interfaces
Angled LCD screen allows users to view data clearly



Electric control module
Standard USB. Optional fingerprint lock, NFC card lock







Access Port
One 25mm test hole







Adjustable foot
Large adjustable feet, easy to level



Integrated lid and handle
Easy to grasp, comfortable to use and durable



Magnetic front cover
Screwless design making it easy to remove and clean the filter

-150°C Cryo Freezer DW-150W209A

Product Details

- **Microprocessor controller**

  Equipped with a microprocessor controller and a 10.1 inch LCD screen with display accuracy at 0.1°C to show the cabinet and ambient temperature, voltage and other data clearly. The temperature inside the cabinet is adjustable from -140°C to -150°C.

- **Safe and secure**

  Integrated handle, equipped with key lock and padlock as standard with optional electromagnetic lock and finger-print lock, providing multiple safeguards for sample safety.

- **Large capacity USB**

  Enables users to download historical temperature data (up to 10 years) for compliance and auditing purposes.

- **Backup power, extended standby**

  Equipped as standard with two lithium batteries which allows extended information/data availability, even after power cutoff.

- **Multiple alarms**

  Including high and low temperature alarm, sensor error, hot condenser, power failure, low battery, door ajar, high ambient temperature and other alarm functions.

- **Superior insulation performance**

  The VIP and polyurethane foam (140mm) cabinet design, multiple door seals, two inner lids to prevent cold loss, delivers excellent thermal efficiencies.

- **Compatible with freezer racks design**

  The internal height of the compartment means that various racks can be used for storage for flexibility.


- **Networking functions**

  A standard RS485 port is configured to be connected to the monitoring software.

- **Anti-defrost design**

  Built-in halo heater reduces frost build-up.


Product Dimension Drawings



Remark:
W0-Total Width
W1-Cabinet Width
W2-Inner Cabinet Effective Width
D0-Total Depth
D1-Inner Cabinet Effective Depth
H0-Total Height
H1-Inner Cabinet Height
H2-Inner Cabinet Effective Height


Model / Code	W0	W1	W2	H0	H1	H2	D0	D1
DW-150W209A	1650mm	1050mm	667mm	1010mm	727mm	677mm	860mm	462mm

Product Accessories (Optional)



Temperature Recorder

- Front-mounted design
- Enables standalone temperature monitoring



LN_2 Backup System

- Interlocked design to turn off LN_2 injection upon door opening
- Protection circuit to prevent battery overcharging
- Lightweight and portable design, suitable for mounting on top of a freezer
- Alarm functions including low battery and sensor fault

Rack Type	ULT Freezer	Freezer Rack						Freezer Rack Quantity	Total Boxes
		CAT.No.	Model	Material	Layout (Rows* Columns)	Box Type	Dimensions (D*W*H) (mm)		
 Chest-type freezer rack	DW-150W209A	433028	DCJ-12-A (SUS304)	SUS304	12*1	2 inch	141*141*662	12	144

Specifications

Model			DW-150W209A
Technical Data	Cabinet Type		Chest
	Climate Class (°C)		10~28
	Cooling Type		Direct Cooling
	Defrost Mode		Manual
	Refrigerant		HC
	Sound Level (dB(A))		55
Performance	Cooling Performance (°C)		-150
	Temperature Range (°C)		-140 ~-150
Control	Controller		Microprocessor
	Display		LCD Touchscreen
Electrical Data	Power Supply (V/Hz)		208~230/60
	Max Power (W)		2000
Dimensions	Capacity (L/Cu.Ft)		209/7.4
	Net/Gross Weight	kg	260/295
		lbs	573.2/650.4
	Interior Dimension (W*D*H)	mm	667*462*677
		in	26.3*18.2*26.7
	Exterior Dimension (W*D*H)	mm	1650*860*1010
		in	65.0*33.9*39.8
	Packing Dimension (W*D*H)	mm	1810*960*1170
		in	71.3*37.8*46.1
	Cabinet Width (without handle and hinge)	mm	667
	Container Load (20'/40'/40'H)		12/24/24
Functions	High/Low Temperature Alarm		Y
	Hot Condenser Alarm		Y
	Power Failure Alarm		Y
	High/Low Voltage Alarm		Y
	Sensor Error Alarm		Y
	Low Battery Alarm		Y
	High Ambient Temperature Alarm		Y
	Door Ajar Alarm		Y
	Start-Up Delay		Y
Accessories	Caster		Y(4)
	Leveling Feet		Y(2)
	Porthole		1*Rear, (25mm)Diameter
	Inner Doors		2
	Freezer Racks Qty (2" boxes)		12
	Capacity (2" boxes)		144
	USB Interface		Y
	Remote Alarm		Y
	5V Power Supply Port		Y
	Temperature Chart Recorder		Optional
	RS232/485 Port		NA/Standard
	CO_2 Backup System		N/A
	LN_2 Backup System		Optional
Other	Certification		UL

*Haier Biomedical reserves the right to change products and specifications without prior notice.